

MANIFATTURA DEL SEVESO SPA unico socio  
STABILIMENTO E SEDE AMMINISTRATIVA  
VIA VESPUCCI N.20  
24046 OSIO SOTTO (BERGAMO) ITALY  
TEL. 0039 035 881950  
FAX 0039 035 4823427  
info@manifatturadelseveso.it  
www.manifatturadelseveso.it  
COD.FISCALE E P.IVA 06007650960  
Capitale sociale EURO 1.000.000,00 i.v.  
Codice meccanografico BG066051  
REG.IMPR.DI BERGAMO N. 06007650960  
R.E.A. N. BG-383192  
PRODUZIONE:  
TESSUTI PER LEGATORIA-  
INDUSTRIA GRAFICA- TESSUTI TECNICI



**Manifattura del Seveso**



February 2019

## **SETALUX® for HP**

**528x700 mm. short grain**

Packets x 100 sheets each

Weight  WET 210 gsm +- 5  DRY 190 gsm +- 2.5  
Thickness 230 micron  
Backing paper 70 gsm.

### **Printing specs**

HP Indigo 12000 press

One shot Print Mode

#### **UNCOATED**

Pressure 900 kg.

Temp. 105 degrees celsius

Press Room Temp. 25 degrees celsius

Press Room Humidity 45% RH

NO PRIMER TO BE ADDED ON MACHINE

Before printing on Setalux® for HP, we recommend to change and use a new blanket .  
Alternatively we suggest at least to change the impression paper and set up machine on 2<sup>nd</sup>  
transfer calibration mood.

### **Ideal Storage Recommendations**

*Keep Relative Humidity at less than 55%.*

*Do not subject Setalux® to abrupt temperature changes.*

*This could affect the relative humidity.*

*When you open the package, please attempt to use every sheet in one print run. If this is not possible, please cover the remaining sheets back up and close the package for the next use.*